

# automotive booths

## EZ PIT DOWNDRAFT AUTOMOTIVE BOOTHS

- EZ TO INSTALL
- EZ TO OPERATE
- EZ TO MAINTAIN

### BELOW GRADE PIT

This Col-Met booth takes in fresh air from the cleaner upper levels of the shop, through a filter bank in the booth ceiling. The filtered air is drawn down and away from the vehicle through exhaust filters in the pit located in the floor. This provides efficient overspray control that reduces prep time and also provides a much healthier workplace environment. An optional above ground basement exhaust plenum is available for installation without concrete work.

The booth can be equipped with an air replacement unit and cure cycles to meet your requirements. It is available in both drive-through and solid-back designs.

### LIGHTING FEATURES

Bright full booth illumination is provided by ten four-tube, 48", 32-watt fluorescent light fixtures in the angled ceiling panels and side walls. Each is sealed behind clear tempered safety glass. All fixtures are UL listed and approved for their intended use and placement. The light tubes are not furnished with the fixtures.

**Col-Met Spray Booth products comply with all OSHA and NFPA regulations.**



Shown with optional basement pit.

### CONSTRUCTION FEATURES AND QUALITY STANDARDS

All booth walls and plenum sections are fabricated from 18-gauge prime quality galvanized steel. The product entry doors are fabricated with tube steel frames hung on structural channel jambs and skinned with 18-gauge galvanized steel. Personnel access doors are provided pre-hung in heavy gauge galvanized steel frames for easy installation. Brixon™ latches are provided for each door opening. All hardware, filters and sealants necessary for installation are included.

Many options such as Control Panels, White Powder Coating, Tri-fold Doors and Observation Windows; just to name a few, are available to customize this booth to your specifications.

### EZ PIT DOWNDRAFT AUTOMOTIVE BOOTHS

Model Number	Interior Dimensions			Exterior Dimensions			Access Doors	Nominal Door Opening				Illumination			Air Flow SCFM	Fan Spec.		Filters	
	Width	Height	Length	Width	Height	Length		Width	Height	Qty	Type	S&G	Open	Total		Dia.	HP	Int.	Exh.
EPD26SB	14'-0"	9'-0"	26'-0"	15'-0"	11'-2"	26'-4"	1	9'-4"	8'-10 1/2"	1	Solid	1	9	10	12,600	30"	3 HP	30	24
EPD26DT	14'-0"	9'-0"	26'-0"	15'-0"	11'-2"	26'-4"	1	9'-4"	8'-10 1/2"	2	Solid	1	9	10	12,600	30"	3 HP	30	24
EPD28SB	14'-0"	9'-0"	28'-0"	15'-0"	11'-2"	28'-4"	1	9'-4"	8'-10 1/2"	1	Solid	1	9	10	12,600	30"	3 HP	30	24
EPD28DT	14'-0"	9'-0"	28'-0"	15'-0"	11'-2"	28'-4"	1	9'-4"	8'-10 1/2"	2	Solid	1	9	10	12,600	30"	3 HP	30	24
EPD30SB	14'-0"	9'-0"	30'-0"	15'-0"	11'-2"	30'-4"	1	9'-4"	8'-10 1/2"	1	Solid	1	9	10	12,600	30"	3 HP	30	24
EPD30DT	14'-0"	9'-0"	30'-0"	15'-0"	11'-2"	30'-4"	1	9'-4"	8'-10 1/2"	2	Solid	1	9	10	12,600	30"	3 HP	30	24



**AutoQuip Canada Ltd.**  
e-mail: sales@autoquip.ca  
toll free: 866-325-2886 // www.autoquip.ca

