

automotive booths

ENVIROFLO® SIDE DOWNDRAFT AUTOMOTIVE BOOTHS

- DOWNDRAFT BENEFITS
- NO PIT REQUIRED

This Col-Met booth intakes fresh air from the cleaner upper levels of the shop through a filter bank in the booth ceiling. The filtered air is drawn down and away from the vehicle through exhaust filters at floor level along both sides. This provides efficient overspray control that reduces prep time and also provides a much healthier workplace environment without an expensive downdraft exhaust pit.

This booth can be equipped with an air replacement unit and cure cycle to meet your requirements. It is available in both drive-through and solid-back designs.

LIGHTING FEATURES

Bright full booth illumination is provided by twelve 48", four-tube, 32-watt fluorescent light fixtures in the angled ceiling panels. Each is mounted behind clear, tempered safety glass and sealed with a gasket. All fixtures are UL listed and approved for their intended use and placement. The light tubes are not furnished with the fixtures.

CONSTRUCTION FEATURES AND QUALITY STANDARDS

All booth and plenum sections are made with 18-gauge galvanized steel. All product and personnel access doors are doubled skinned for ease of maintenance. Brixon™ latches and limit switches are provided for each door opening.



Exhaust is provided by a 30" diameter tubeaxial fan with a three-phase motor. An access panel under the fan is provided for maintenance purposes. The single fan design is quieter and requires less maintenance. The control panel and other electrical components may be purchased separately. All hardware, filters and sealants needed for booth installation are included.

Col-Met Spray Booth products comply with all OSHA and NFPA regulations.

There will be no surprise additions required to meet the codes.

ENVIROFLO SIDE DOWNDRAFT AUTOMOTIVE BOOTHS

Model Number	Interior Dimensions			Exterior Dimensions			Access Doors	Nominal Door Opening				Illumination			Air Flow SCFM	Fan Spec.		Filters	
	Width	Height	Length	Width	Height	Length		Width	Height	Qty	Type	S&G	Open	Total		Dia.	HP	Int.	Exh.
EF26SB	13'-0"	8'-10"	26'-0"	16'-4"	10'-6"	26'-4"	1	9'-4"	8'-10"	1	TF	1	11	12	11,900	30"	3 HP	54	24
EF26DT	13'-0"	8'-10"	26'-0"	16'-4"	10'-6"	26'-4"	1	9'-4"	8'-10"	2	TF	1	11	12	11,900	30"	3 HP	54	24
EF28SB	13'-0"	8'-10"	28'-0"	16'-4"	10'-6"	28'-10"	1	9'-4"	8'-10"	1	TF	0	12	12	12,968	30"	5 HP	54	24
EF28DT	13'-0"	8'-10"	28'-0"	16'-4"	10'-6"	28'-10"	1	9'-4"	8'-10"	2	TF	0	12	12	12,968	30"	5 HP	54	24
EF31SB	13'-0"	8'-10"	31'-0"	16'-4"	10'-6"	31'-4"	1	9'-4"	8'-10"	1	TF	1	11	12	14,105	30"	5 HP	54	24
EF31DT	13'-0"	8'-10"	31'-0"	16'-4"	10'-6"	31'-4"	1	9'-4"	8'-10"	2	TF	1	11	12	14,105	30"	5 HP	54	24



AutoQuip Canada Ltd.
 e-mail: sales@autoquip.ca
 toll free: 866-325-2886 // www.autoquip.ca

