

# automotive booths

## EZ-26 MODIFIED DOWNDRAFT AUTOMOTIVE BOOTHS

- EZ TO INSTALL
- EZ TO OPERATE
- EZ TO MAINTAIN
- EZ TO PRESSURIZE
- EZ TO QUICK SHIP

The Col-Met EZ-26 Modified Downdraft Booth intakes fresh air from the cleaner upper levels of the shop through a filter bank located in the booth ceiling near the product doors. The filtered air is drawn down through the booth to an exhaust filter system at the other end. This booth is equipped with a pre-filter plenum for additional intake air filtration.

The basic modified downdraft design allows for easy pressurization with the addition of an intake fan or a heated air make up unit.

### LIGHTING FEATURES

Bright full booth illumination is provided by ten four-tube, 48", 32-watt, fluorescent light fixtures in the angled ceiling panels and side walls. Each is sealed behind clear tempered safety glass. All fixtures are UL listed and approved for their intended use and placement. The light tubes are not furnished with the fixtures.

### CONSTRUCTION FEATURES AND QUALITY STANDARDS

All booth and plenum sections are made with 18-gauge galvanized steel. All product and personnel access doors are pre-hung in heavy



Optional powder coat finish shown.

gauge galvanized steel frames for easy installation. Brixon™ latches are provided for each door opening.

Exhaust is provided by a 30" diameter tubeaxial fan with a 3 HP, three-phase motor.

All hardware, filters and sealants needed for the booth installation are included. The control panel and other electrical components may be purchased separately.

**Col-Met Spray Booth products comply with all OSHA and NFPA regulations.**

### EZ-26 MODIFIED DOWNDRAFT AUTOMOTIVE BOOTHS

Model Number	Interior Dimensions			Exterior Dimensions			Access Doors	Nominal Door Opening				Lights Open	Air Flow SCFM	Fan Spec.		Filters	
	Width	Height	Length	Width	Height	Length		Width	Height	Qty	Type			Dia.	HP	Int.	Exh.
EMD26SB	14'-0"	9'-0"	26'-0"	14'-4"	10'-10"	26'-4"	1	9'-4"	8'-10 1/2"	1	Solid	10	12,600	30"	3HP	23	16
EMD26PSB	14'-0"	9'-0"	26'-0"	14'-4"	10'-10"	26'-4"	1	9'-4"	8'-10 1/2"	1	Solid	10	12,600	30"	3HP	15	16



**AutoQuip Canada Ltd.**

e-mail: [sales@autoquip.ca](mailto:sales@autoquip.ca)

toll free: 866-325-2886 // [www.autoquip.ca](http://www.autoquip.ca)