

automotive booths

EZ-26 SIDE DOWNDRAFT AUTOMOTIVE BOOTHS

- EZ TO INSTALL
- EZ TO OPERATE
- EZ TO MAINTAIN
- EZ TO PRESSURIZE

NO PIT NEEDED

This Col-Met Booth intakes fresh air from the cleaner upper levels of the shop through a filter bank in the booth ceiling. The filtered air is drawn down and away from the vehicle through exhaust filters at the floor level, along both sides. This provides efficient overspray control that reduces prep time and also provides a much healthier workplace environment without an expensive downdraft exhaust pit. When purchased as a pressurized unit, the booth can be equipped with an air replacement unit and cure cycle to meet your requirements. It is available in both drive-through and solid-back designs.

LIGHTING FEATURES

Bright full booth illumination is provided by ten four-tube, 48", 32-watt, fluorescent light fixtures in the angled ceiling panels and side walls. Each is sealed behind clear, tempered safety glass. All fixtures are UL listed and approved for their intended use and placement. The light tubes are not furnished with the fixtures.

CONSTRUCTION FEATURES AND QUALITY STANDARDS

All booth and plenum sections are made with 18-gauge galvanized steel. Personnel access doors



are pre-hung in heavy gauge galvanized frames for easy installation. Brixon™ latches are provided for each door opening.

Exhaust is provided by two 24" diameter tubeaxial fans with 2 HP, three-phase motors.

All hardware, filters and sealants needed for the booth installation are included. The control panel and other electrical components may be purchased separately.

Col-Met Spray Booth products comply with all OSHA and NFPA regulations.

EZ-26 SIDE DOWNDRAFT AUTOMOTIVE BOOTHS

Model Number	Interior Dimensions			Exterior Dimensions			Access Doors	Nominal Door Opening				Lights Open	Air Flow SCFM	Fan Spec.		Filters	
	Width	Height	Length	Width	Height	Length		Width	Height	Qty	Type			Dia.	HP	Int.	Exh.
ESD26SB	14'-0"	9'-0"	26'-0"	16'-4"	9'-4"	26'-4"	1	9'-4"	8'-10 1/2"	1	Solid	10	12,600	(2) 24"	2HP	32	20
ESD26SBPF	14'-0"	9'-0"	26'-0"	16'-4"	11'-2"	26'-4"	1	9'-4"	8'-10 1/2"	1	Solid	10	12,600	(2) 24"	2HP	56	20
ESD26PSB	14'-0"	9'-0"	26'-0"	16'-4"	11'-2"	26'-4"	1	9'-4"	8'-10 1/2"	1	Solid	10	12,600	(2) 24"	2HP	32	20
ESD26DT	14'-0"	9'-0"	26'-0"	16'-4"	9'-4"	26'-4"	1	9'-4"	8'-10 1/2"	2	Solid	10	12,600	(2) 24"	2HP	32	20
ESD26PDT	14'-0"	9'-0"	26'-0"	16'-4"	11'-2"	26'-4"	1	9'-4"	8'-10 1/2"	2	Solid	10	12,600	(2) 24"	2HP	32	20



AutoQuip Canada Ltd.
 e-mail: sales@autoquip.ca
 toll free: 866-325-2886 // www.autoquip.ca

